



CAUTION
 TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.

NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005

NOTE: THE SURFACE OF THE INSULATED WIRES MARKED (X) TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.

WIRING NOTE
 ALL WIRES #14 AWG, TYPE SEW/SF2 MINIMUM UNLESS OTHERWISE NOTED

LT3K
 240V 60HZ
 KILN SITTER
 W/LIM. TIMER
 & 4" TUBE
 ASSY KS7

CR6
 6-2/8-1 CORDSET
 6-50P CAP

POWER REQ'TS
 240 VOLTS
 1 PHASE
 60 HERTZ
 40 AMPS
 9600 WATTS

| TO RE-ORDER ELEMENTS, SPECIFY | | |
|-------------------------------|-----|---------|
| DESCRIPTION | QTY | LOC |
| ELS233TB | 2 | TOP&BOT |
| ELS233M | 2 | MIDDLE |
| | | |

UL/CUL LISTED MAX. TEMP. 2350° F

| | | | | |
|----------|--------------------------------------------------------------------------|------------------------------------------------------------------------------------|----------------|-----|
| COMMENTS | PARAGON INDUSTRIES 2011 SOUTH TOWN EAST BLVD MESQUITE, TEXAS 75149 | PRODUCT DESCRIPTION 10 SIDES, 22.5"DIA, 22.25"DP 240V, 1PH, 60HZ, 40A, 9600W | PART NO. | REV |
| | | | S233 | - |
| | | | WIRING DIAGRAM | |