



CAUTION
 TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.

NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005

NOTE: THE SURFACE OF THE INSULATED WIRES MARKED ⊗ TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.

WIRING NOTE
 ALL WIRES #14 AWG, TYPE SEW/SF2 MINIMUM UNLESS OTHERWISE NOTED

LT3K
 240V 60HZ
 KILN SITTER
 W/LIM. TIMER
 & 4" TUBE
 ASSY KS7

CR6
 6-2/8-1 CORDSET
 6-50P CAP

POWER REQ'TS
 240 VOLTS
 1 PHASE
 60 HERTZ
 45 AMPS
 10800 WATTS
 MAX TEMP 2300° F

UL/CUL LISTED

TO RE-ORDER ELEMENTS, SPECIFY		
DESCRIPTION	QTY	LOC
ELS24TBM	6	TOP, BOT & MID

COMMENTS	PARAGON INDUSTRIES 2011 SOUTH TOWN EAST BLVD MESQUITE, TEXAS 75149	PRODUCT DESCRIPTION	PART NO.	REV
		10 SIDES, 23.5" DIA, 29" DP 240V, 1PH, 60HZ, 45A, 10800W	S24	-
			WIRING DIAGRAM	