

**CAUTION**


TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.

NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005

NOTE: THE SURFACE OF THE INSULATED WIRES MARKED ⊗ TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.

**WIRING NOTE**

ALL WIRES #14 AWG, TYPE SEW/SF2 MINIMUM UNLESS OTHERWISE NOTED



**POWER REQ'TS**  
 240 VOLTS  
 1 PHASE  
 60 HERTZ  
 30 AMPS  
 7200 WATTS  
 MAX TEMP 2350° F

TO RE-ORDER ELEMENTS, SPECIFY		
DESCRIPTION	QTY	LDC
ELSNF823TB	4	TOP & BOTT
ELSNF823M	4	MID

UL LISTED

COMMENTS

PARAGON INDUSTRIES  
 2011 SOUTH TOWN EAST BLVD  
 MESQUITE, TEXAS 75149

**PRODUCT DESCRIPTION**  
 8 SIDES, 16.5" DIA, 22.25" DP  
 240V, 1PH, 60HZ, 30A, 7200W

PART NO.	SNF823	REV	-
WIRING DIAGRAM			