



Paragon Industries, L.P.
 2011 South Town East Blvd.
 Mesquite, Texas
 75149-1122
 972-288-7557

www.paragonweb.com
 info@paragonweb.com

FiberFuse-16

- Light-weight ceramic fiber lid for easy loading
- A steel cover with welded corners protects the top of the lid.
- Slotted control panel for air circulation
- Surface-mounted sinusoidal elements eliminate element grooves and therefore take maximum advantage of the wall insulation.
- Runs on standard 120 v outlet.
- Fast-response, exposed-tip 1/4" wide thermocouple
- Wooden lid handle stays cool.
- Mechanical relay or optional deluxe mercury relay
- Sloped switch box for easy operation of the digital controller
- Ships by convenient UPS.
- Lid safety switch shuts off power to elements when lid is opened.
- Mar-proof rubber feet
- Colorful 28-page kiln instruction manual and a separate controller manual



Dimensions & Specifications

Max Temp °F	1700°
Cubic Feet	.88
Firing Chamber	16" Square x 6"D
Uncrated Outside Dimensions	30"W x 21"D x 13"H
Shipping Wt., Kiln	100
Shipping Wt., Furniture	16
Doorway Clearance Needed	20
Volts	120
Amps	15
Watts	1,800
Circuit: Copper Wire Size	12
Circuit: Fuse	20
NEMA Config.	5-15R