



CAUTION
 TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.

NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005

NOTE: THE SURFACE OF THE INSULATED WIRES MARKED ⊗ TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.

WIRING NOTE
 ALL WIRES #14 AWG, TYPE SEW/SF2 MINIMUM UNLESS OTHERWISE NOTED

LT3K
 240V 60HZ
 KILN SITTER
 W/LIM. TIMER
 & 4" TUBE
 ASSY KS7

CR6
 6-2/8-1 CORDSET
 6-50P CAP

POWER REQ'TS
 240 VOLTS
 1 PHASE
 60 HERTZ
 45 AMPS
 10800 WATTS
 MAX TEMP 2300° F

| TO RE-ORDER ELEMENTS, SPECIFY | | |
|-------------------------------|-----|----------------|
| DESCRIPTION | QTY | LOC |
| ELS24TBM | 6 | TOP, BOT & MID |
| | | |
| | | |

UL/CUL LISTED

| | | | | | |
|----------|--|---|--|--------------|-------|
| COMMENTS | PARAGON INDUSTRIES 2011 SOUTH TOWN EAST BLVD MESQUITE, TEXAS 75149 | PRODUCT DESCRIPTION 10 SIDES, 23.5" DIA, 29" DP 240V, 1PH, 60HZ, 45A, 10800W | | PART NO. S24 | REV - |
| | | WIRING DIAGRAM | | | |