

CAUTION

TO PROVIDE CONTINUED PROTECTION AGAINST THE RISK OF ELECTRIC SHOCK, CUSTOMER'S POWER SUPPLY MUST BE PROPERLY GROUNDED.

NOTE: GROUNDING SCREW TO HAVE A GREEN COLORED SLOTTED AND/OR HEX HEAD NO SUBSTITUTES. USE #1005

NOTE: THE SURFACE OF THE INSULATED WIRES MARKED (X) TO BE COLORED GREEN, WITH OR WITHOUT ONE OR MORE YELLOW STRIPES.

CR21
10/3 CORDSET
6-30P CAP

POWER REQ'TS

240 VOLTS
1 PHASE
60 HERTZ
26.7 AMPS
6400 WATTS

MAX TEMP 2350° F

PY50
TYPE K T/C

TF3
30A RELAY
W/12V
DC COIL

TF2
CONTROL
TRANSFORMER
OUTPUT=24VAC

TF21
DTC 1000C

1/2 AMP FUSE

UL/CUL LISTED

WIRING NOTE

ALL WIRES #12 AWG,
TYPE SEW/SF2 MINIMUM
UNLESS OTHERWISE NOTED

TO RE-ORDER ELEMENTS, SPECIFY		
DESCRIPTION	QTY	LOC
ELTNF1613	3	TOP, BOT & MID

COMMENTS

PARAGON INDUSTRIES
2011 SOUTH TOWN EAST BLVD
MESQUITE, TEXAS 75149

PRODUCT DESCRIPTION
8 SIDES, 16.5" DIA, 13.25" DP
240V, 1PH, 60HZ, 27A, 6400W

PART NO. TNF1613

REV -

WIRING DIAGRAM